



NOTES

1. 30 FOOT MINIMUM DISTANCE TO TREES OR LANDSCAPING OVER 2 FEET IN HEIGHT.
2. CONSTRUCT MAINTENANCE EDGE PER STANDARD DRAWING 1109.
3. 8 INCH MOUNTABLE CONCRETE CURB PER APWA STANDARD PLAN 121-1.
4. MINIMUM MEDIAN WIDTH SHALL BE 16 FEET FOR EMERGENCY VEHICLE TURN-AROUND.
5. FOR NEW EMERGENCY VEHICLE MEDIAN TURN-AROUND ON EXISTING STREETS, 12 INCHES OF EXISTING ASPHALT FROM THE MEDIAN SHALL BE REMOVED AND REPLACED IN KIND.
6. THE LOCATION OF TURN-AROUND SHALL BE MID-POINT BETWEEN STREET CENTERLINE OR AS REQUIRED BY THE CITY ENGINEER.



APPROVED BY:				
<i>John P. Sullivan</i>				
JOHN P. SULLIVAN		24079	8/08/06	
CITY ENGINEER		RCE	DATE	
RECOMMENDED:				
<i>John P. Sullivan</i>				
JOHN P. SULLIVAN		44485	8/07/06	
ASSISTANT CITY ENGINEER		RCE	DATE	
REV	DESCRIPTION	BY	APP'D	DATE

CITY OF ONTARIO		STANDARD DRAWING NUMBER
MAINTENANCE VEHICLE MEDIAN TURN-OUT		
		1218